Steel band covers

Continuous, cost-effective protection against chips and other external influences


Trademarks are legally protected for TSUBAKI KABELSCHLEPP GmbH as a national or international registration in the following countries: tsubaki-kabelschlepp.com/trademarks

Steel band covers | Overview

Steel band covers

To protect the cables against flying sparks, radiated heat and small chips, steel band covers made from corrosionresistant and acid-resistant spring band steel are available.

- » Cost-effective cover variant for half-stayed version
- » Maximum steel band width: 1000 mm



Guiding of the steel band:

with steel band holders on the inside of the side band

Fastening of the steel band:

Inside: with steel band holders on the end connectors

Outside: with the fastening screws of the end connectors


Dimensions table

Туре	Steel band length [mm]		Steel band width [mm]
	Outer steel band	Inner steel band	
S/SX 0650	L _k +280	L _k + 130	B _k – 22
S/SX 0950	L _k + 360	L _k + 150	B _k – 27
S/SX 1250	L _k + 470	L _k + 170	B _k - 34
S/SX 1800	L _k +640	L _k + 200	B _k – 40
S/SX 2500	L _k +945	L _k + 255	B _k – 46

Steel band covers for the other types on request!

Subject to change without notice.









Fastening on the cable carrier connection with special end connector.

MT

XLT series

ROBOTRAX® System

FLATVEYOR®

CLEANVEYOR®

LS/LSX series

S/SX series

S/SX-Tubes series

Accessories