

UNIFLEX *Advanced* series


Light, quiet all-rounder with a
wide range of applications*



* Some features can be different
for certain types for design reasons.

Trademarks are legally protected for the TSUBAKI KABELSCHLEPP GmbH as
a national or international registration in the following countries:
tsubaki-kabelschlepp.com/trademarks


Subject to change without notice.



- | | | | |
|--|---|--|--|
| <p>1 Universal mounting bracket (UMB) with integratable strain relief comb</p> <p>2 Designs with inside or outside opening stays</p> <p>3 Extremely fast and easy to open due to ball joint mechanism</p> | <p>4 Top-mounted frame stay</p> <p>5 Single-part links (type 020)</p> <p>6 Favourable ratio of inner to outer width</p> <p>7 Many separation options for the cables</p> | <p>8 Robust double-stroke system for long unsupported lengths</p> <p>9 Easy divider fixing</p> <p>10 Very quiet through integrated noise damping</p> <p>11 Lateral wear surfaces</p> | <p>12 Single-part end connectors with integratable strain relief comb</p> |
|--|---|--|--|

Features

- » Extensive unsupported lengths
- » High torsional rigidity
- » Good ratio of inner to outer width
- » Numerous custom material types for custom applications available
- » Easy assembly and fast cable laying
- » Assembly tools available
- » Stays with ball joint opening on both sides
- » Many possibilities for internal subdivision
- » Wear surfaces for gliding applications with extended travel lengths



Fixable dividers for arrangements rotated by 90° and applications with high lateral accelerations – no additional spacers required



Lateral wear surfaces – for long service life for applications where the carrier is rotated through 90°



Simple fixing of strain relief comb or C-Rail in the connector

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series

TKK series

EasyTrax® series

Type	Opening variant	Stay variant	h _i [mm]	h _G [mm]	B _i [mm]	B _k [mm]	B _i - grid [mm]	t [mm]	KR [mm]	Additional load ≤ [kg/m]	Cable- d _{max} [mm]
UA1250											
		020	17.5	23	30 - 50	60	-	25	28 - 100	4	14
UA1320											
		020	20	25.5	15 - 65	27 - 77	-	32	28 - 125	3.0	16
UA1455											
		020	26	36	25 - 130	41 - 146	-	45.5	52 - 200	6	20.5
		030	26	36	25 - 130	41 - 146	-	45.5	52 - 200	6	20.5
		040	26	36	25 - 130	41 - 146	-	45.5	52 - 200	6	20.5
UA1555											
		020	38	50	50 - 150	68 - 168	-	55.5	63 - 200	10	30
		030	38	50	50 - 150	68 - 168	-	55.5	63 - 200	10	30
		040	38	50	50 - 150	68 - 168	-	55.5	63 - 200	10	30
UA1665											
		020	44	60	50 - 250	72 - 272	-	66.5	75 - 300	15	35
		030	44	60	50 - 250	72 - 272	-	66.5	75 - 300	15	35
		040	44	60	50 - 250	72 - 272	-	66.5	75 - 300	15	35
		RMAI	44 (114-189)	60 (170-245)	125 - 200	147 - 222	1	66.5	200 - 300	15	35/151
		RMAO	44 (114-189)	60 (170-245)	125 - 200	147 - 222	1	66.5	75 - 300	15	35/151

Unsupported arrangement			Gliding arrangement			Inner Distribution				Movement			Page
Travel length ≤ [m]	$v_{max} \leq [m/s]$	$a_{max} \leq [m/s^2]$	Travel length ≤ [m]	$v_{max} \leq [m/s]$	$a_{max} \leq [m/s^2]$	TS0	TS1	TS2	TS3	vertical hanging or standing	lying on the side	rotating arrangement	
													
1,6	10	50	60	3	30	•	-	-	-	•	•	•	152
2,9	10	50	80	2,5	25	•	-	-	-	•	•	•	158
4,8	10	50	120	2,5	20	•	-	-	•	•	•	•	164
4,8	10	50	120	2,5	20	•	•	-	•	•	•	•	165
4,8	10	50	-	-	-	•	•	-	•	•	•	•	166
6,3	9	45	125	3	20	•	-	-	•	•	•	•	174
6,3	9	45	125	3	20	•	•	-	•	•	•	•	175
6,3	9	45	-	-	-	•	•	-	•	•	•	•	176
7	8	40	150	3	15	•	-	-	•	•	•	•	184
7	8	40	150	3	15	•	•	-	•	•	•	•	185
7	8	40	-	-	-	•	•	-	•	•	•	•	186
7	8	40	150	3	15	•	•	-	•	•	•	-	188
7	8	40	150	3	15	•	•	-	•	•	•	-	190

Subject to change without notice.

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series

TKK series

EasyTrax® series

	Cable carrier	Cable carrier configuration	Configuration guidelines	Materials information	MONO series	QuickTrax® series	UNIFLEX Advanced series	TKP35 series	TKK series	EasyTrax® series	
Type	Opening variant	Stay variant	h_i [mm]	h_G [mm]	B_i [mm]	B_k [mm]	B_i -grid [mm]	t [mm]	KR [mm]	Additional load ≤ [kg/m]	Cable- d_{max} [mm]
UA1775											
		020	56	77	100 - 400	126 - 476	-	77.5	90 - 340	25	44
		030	56	77	100 - 400	126 - 476	-	77.5	90 - 340	25	44
		040	56	77	100 - 400	126 - 476	-	77.5	90 - 340	25	44
UA1995											
		020	80	110	85 - 250	115 - 280	-	99.5	150 - 500	50	64
		030	80	110	85 - 250	115 - 280	-	99.5	150 - 500	50	64
		040	80	110	85 - 250	115 - 280	-	99.5	150 - 500	50	64
		070	80	110	85 - 250	115 - 280	-	99.5	150 - 500	50	64

Subject to change without notice.

Unsupported arrangement			Gliding arrangement			Inner Distribution				Movement			Page
Travel length ≤ [m]	v_{max} ≤ [m/s]	a_{max} ≤ [m/s ²]	Travel length ≤ [m]	v_{max} ≤ [m/s]	a_{max} ≤ [m/s ²]	TS0	TS1	TS2	TS3	vertical hanging or standing	lying on the side	rotating arrangement	
6.8	10	35	200	3	8	•	-	-	•	•	•	•	198
6.8	10	35	200	3	8	•	•	-	•	•	•	•	199
6.8	10	35	200	3	8	•	•	-	•	•	•	•	200
9	10	25	200	8	20	•	-	-	•	•	•	•	206
9	10	25	200	8	20	•	•	-	•	•	•	•	207
9	10	25	200	8	20	•	•	-	•	•	•	•	208
9	10	25	200	8	20	•	•	-	•	•	•	•	209

Cable carrier

Cable carrier
configuration

Configuration
guidelines

Materials
information

MONO
series

QuickTrax®
series

UNIFLEX
Advanced
series

TKP35
series

TKK
series

EasyTrax®
series

UA1250



Pitch
25 mm



Inner height
17,5 mm



Inner widths
30 – 50 mm



Bending radii
28 – 100 mm

Stay variants



Design 020 page 158

Closed frame


- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



QuickTrax® | EasyTrax®

For an openable cable carrier with 16.5 – 17.6 mm inner height we recommend the series QuickTrax® 0250 or EasyTrax® 0250 QT0250 from page 132 and ET0250 from page 246.

Unsupported arrangement




KR [mm]	H [mm]	H _z [mm]	L _B [mm]	U _B [mm]
28	79	104	138	65
38	99	124	169	75
45	113	138	191	82
60	143	168	238	97
75	173	198	286	112
100	223	248	364	137

Load diagram for unsupported length depending on the additional load.

Sagging of the cable carrier is technically permitted for extended travel lengths, depending on the specific application.

Intrinsic cable carrier weight $q_k = 0.36 \text{ kg/m}$ with $B_i 50 \text{ mm}$. For other inner widths, the maximum additional load changes.



Speed
up to 10 m/s



Acceleration
up to 50 m/s^2




Travel length
up to 1.6 m



Additional load
up to 4 kg/m

Gliding arrangement



Speed
up to 3 m/s



Acceleration
up to 30 m/s^2



Travel length
up to 60 m



Additional load
up to 4kg/m



The gliding cable carrier must be guided in a channel.
See p. 866.

Cable carrier
Cable carrier configuration
Configuration guidelines
Materials information
MONO series
QuickTrax® series
UNIFLEX Advanced series
TKP35 series
TKK series
EasyTrax® series

Stay variant 020 – closed frame


- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 30 – 50 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_g [mm]	B_i [mm]		B_k [mm]	KR [mm]						q_k [kg/m]
17.5	23	30	50	$B_i + 10$	28	38	45	60	75	100	0.32 – 0.36

Order example



UA1250
Type

020
Stay variant

50
 B_i [mm]

75
 KR [mm]

1100
 L_k [mm]

VS
Stay arrangement

Divider systems


The divider system is mounted on every 2nd chain link as a standard.

As a standard, dividers or the complete divider system (dividers with height separations) are movable in the cross section (**version A**).

For applications with lateral accelerations and applications with the cable carrier rotated by 90°, the dividers can easily be fixed on the stay through rotation.

The arresting cams snap into the catch profiles in the covers (**version B**).

Divider system TSO without height separation



Order example



TSO

Divider system

•

A

Version

•

3

n_T

Please state the designation of the divider system (TSO), the version, and the number of dividers per cross section [n_T]. You are welcome to add a sketch to your order.

Cable carrier
Cable carrier configuration
Configuration guidelines
Materials information
MONO series
QuickTrax® series
UNIFLEX Advanced series
TKP35 series
TKK series
EasyTrax® series

Additional product information online




Installation instructions, etc.:
Additional info via your smartphone or
check online at
[tsubaki-kabelschlepp.com/
downloads](https://tsubaki-kabelschlepp.com/downloads)



Configure your cable carrier here:
online-engineer.de


Single-part end connectors – plastic (with integrated strain relief)

The plastic end connectors can be connected **from above or below**. The connection type can be changed by altering the position of the end connector.



▲ Assembly options

B_i [mm]	B_{EF} [mm]	n_z
30	40	2
50	60	4



Connection point
F – fixed point
M – driver

Connection type
A – threaded joint outside (standard)
I – threaded joint inside
H – threaded joint, rotated 90° to the outside
K – threaded joint, rotated 90° to the inside

Order example

End connector	.	F	A
End connector	.	M	A
		Connection point	Connection type

Subject to change without notice.



EasyTrax® series	TKK series	TKP35 series	UNIFLEX Advanced series		QuickTrax® series	MONO series	Materials information	Configuration guidelines	Cable carrier configuration	Cable carrier
---------------------	---------------	-----------------	-------------------------------	--	----------------------	----------------	--------------------------	-----------------------------	--------------------------------	---------------

UA1320



Pitch
32 mm



Inner height
20 mm



Inner widths
15 – 65 mm



Bending radii
28 – 125 mm

Stay variants



Design 020 page 158

Closed frame


- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



QuickTrax® | EasyTrax®

For an openable cable carrier with 18 – 20 mm inner height we recommend the series QuickTrax® 0320 or EasyTrax® 0320 QT0320 from page 138 and ET0320 from page 252.

Unsupported arrangement



KR [mm]	H [mm]	H _z [mm]	L _B [mm]	U _B [mm]
28	81.5	98.5	152	73
38	101.5	118.5	184	83
48	121.5	138.5	215	93
75	175.5	192.5	300	120
100	225.5	242.5	379	145
125	275.5	292.5	457	170

Load diagram for unsupported length depending on the additional load.

Sagging of the cable carrier is technically permitted for extended travel lengths, depending on the specific application.

Intrinsic cable carrier weight $q_k = 0.40 \text{ kg/m}$ with $B_i 50 \text{ mm}$. For other inner widths, the maximum additional load changes.



Speed
up to 10 m/s




Acceleration
up to 50 m/s^2




Travel length
up to 2.9 m



Additional load
up to 3 kg/m



Gliding arrangement



Speed
up to 2.5 m/s



Acceleration
up to 25 m/s^2



Travel length
up to 80 m



Additional load
up to 3 kg/m



The gliding cable carrier must be guided in a channel.
See p. 866.

Cable carrier

Cable carrier
configuration

Configuration
guidelines

Materials
information

MONO
series

QuickTrax®
series

UNIFLEX
Advanced
series

TKP35
series

TKK
series

EasyTrax®
series

Stay variant 020 – closed frame


- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 15 – 65 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k
rounded to pitch t

h_i [mm]	h_G [mm]	B_i [mm]					B_k [mm]	KR [mm]					q_k [kg/m]	
20	25.5	15	25	38	50	65	$B_i + 12$	28	38	48	75	100	125	0.36–0.48

Order example



UA1320

Type

020

Stay variant

50

B_i [mm]

100

KR [mm]

960

L_k [mm]

VS

Stay arrangement

Divider systems


The divider system is mounted on every 2nd chain link as a standard.

As a standard, dividers or the complete divider system (dividers with height separations) are movable in the cross section (**version A**).

Divider system TSO without height separation

Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	n _T min
A	4	8	6	-

The dividers can be moved in the cross section.



Order example



TSO . A . 3
Divider system Version n_T

Please state the designation of the divider system (**TSO**), the version, and the number of dividers per cross section [n_T]. You are welcome to add a sketch to your order.

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series



TKP35 series

TKK series


EasyTrax® series

Single-part end connectors – plastic (with integrated strain relief)


The plastic end connectors can be connected from above or below. The connection type can be changed by altering the position of the end connector.



Bi: 25




Bi: 38/50/65




▲ Assembly options

B_i [mm]	B_{EF} [mm]	n_z
15	27	2
25	37	3
38	50	4
50	62	5
65	77	6



The end connectors are also available as an option **without** integrated strain relief. Please state when ordering.



Connection point

F – fixed point
M – driver


Connection type

A – threaded joint outside (standard)
I – threaded joint inside
H – threaded joint, rotated 90° to the outside
K – threaded joint, rotated 90° to the inside

Order example



End connector	F	A
End connector	M	A
End connector	Connection point	Connection type



Subject to change without notice.

EasyTrax® series	TKK series	TKP35 series	UNIFLEX Advanced series	QuickTrax® series	MONO series	Materials information	Configuration guidelines	Cable carrier configuration	Cable carrier
---------------------	---------------	-----------------	-------------------------------	----------------------	----------------	--------------------------	-----------------------------	--------------------------------	---------------

UA1455



Pitch
45.5 mm



Inner height
26 mm



Inner widths
25 – 130 mm



Bending radii
52 – 200 mm

Stay variants



Design 020 page 164

Closed frame

- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Design 030 page 165

Frame with outside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Outside:** openable and detachable.



Design 040 page 166

Frame with inside detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Inside:** openable and detachable.



EasyTrax®

For an openable cable carrier with 25 mm inner height we recommend the series EasyTrax® 1455 ET1455 from page 258.

Unsupported arrangement




KR [mm]	H [mm]	H _z [mm]	L _B [mm]	U _B [mm]
52	140	165	255	116
65	166	191	296	129
95	226	251	390	159
125	286	311	484	189
150	336	361	563	214
180	396	421	657	244
200	436	461	720	264

Load diagram for unsupported length depending on the additional load.

Sagging of the cable carrier is technically permitted for extended travel lengths, depending on the specific application.

Intrinsic cable carrier weight $q_k = 0.75 \text{ kg/m}$ with $B_0 38 \text{ mm}$. For other inner widths, the maximum additional load changes.



Speed
up to 10 m/s



Acceleration
up to 50 m/s^2




Travel length
up to 4.8 m



Additional load
up to 6 kg/m

Gliding arrangement | G0 module with chain links optimized for gliding



KR [mm]	H [mm]	G0 module RKR [mm]	L _B [mm]	U _B [mm]
52	108	225	780	377
65	108	225	825	389
95	108	225	1007	450
125	108	225	1189	508
150	108	225	1371	573
180	108	225	1599	655
200	108	225	1781	723



Speed
up to 2.5 m/s



Acceleration
up to 20 m/s^2



Travel length
up to 120 m



Additional load
up to 6 kg/m



The gliding cable carrier must be guided in a channel.
See p. 866.

The G0 module mounted on the driver is a defined sequence of 5 adapted KR/RKR link plates.

Glide shoes must be used for gliding applications.

Only designs 020 and 030 can be used for a gliding arrangement.

Cable carrier

Cable carrier
configuration

Configuration
guidelines

Materials
information

MONO
series

QuickTrax®
series

UNIFLEX
Advanced
series

TKP35
series

TKK
series

EasyTrax®
series

Stay variant 020 – closed frame


- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 25 – 130 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t



Special version for support legs of commercial vehicles

Special versions for the safe guiding and separating of rigid hydraulic hoses and electric cables in a limited space in extendable support feet of commercial vehicles on request.

h_i [mm]	h_G [mm]	h_G' [mm]	B_i [mm]			B_k [mm]	B_{EF} [mm]	KR [mm]				q_k [kg/m]
26	36	38.5	25	38	58	$B_i + 16$	$B_i + 19$	52	65	95	125	0.71 – 1.12
			78	103	130			150	180	200		

Order example



UA1455
Type

020
Stay variant

78
 B_i [mm]


150
 KR [mm]

1456
 L_k [mm]

VS
Stay arrangement

Stay variant 030 – with outside opening and detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » Swivable and detachable left or right in any position.
- » **Outside:** openable and detachable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 25 – 130 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_G [mm]	$h_{G'}$ [mm]	B_i [mm]			B_k [mm]	B_{EF} [mm]	KR [mm]				q_k [kg/m]
26	36	38.5	25	38	58	$B_i + 16$	$B_i + 19$	52	65	95	125	0.73 – 1.10
			78	103	130			150	180	200		

Order example



UA1455	030	78	150	1456	VS
Type	Stay variant	B_i [mm]	KR [mm]	L_k [mm]	Stay arrangement

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series

TKK series

EasyTrax® series

Stay variant 040 – with inside opening and detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » Swivable and detachable left or right in any position.
- » **Inside:** openable and detachable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 25 – 130 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.



Design 040 is not suitable for gliding arrangements.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_g [mm]	B_i [mm]			B_k [mm]	KR [mm]				q_k [kg/m]
26	36	25	38	58	$B_i + 16$	52	65	95	125	0.73 - 1.10
		78	103	130		150	180	200		

Order example



UA1455
Type

040
Stay variant

78
 B_i [mm]

150
 KR [mm]

1456
 L_k [mm]

VS
Stay arrangement

Divider systems

The divider system is mounted on every 2nd chain link as a standard.


As a standard, dividers or the complete divider system (dividers with height separations) are movable in the cross section (**version A**).

For applications with lateral acceleration and lying on the side, divider with arresting cams are available.
The locking cams click into place in the locking grids in the stays (**version B**).

Divider system TSO without height separation

Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	a _x grid [mm]	η _T min
A	3.5	7	5	-	-
B*	4/5**	7.5	5.5	2.5	-


Number of dividers for design Q20 depending on B_i
* not for design Q20
** 4 mm for B_i 38 - 103; 5 mm for B_i 25, 130



Divider system TS1 with continuous height separation*

Vers.	a _T min [mm]	a _T max [mm]	a _x min [mm]	a _c min [mm]	a _x grid [mm]	η _T min
A	3.5	20	7	5	-	2
B	4/5**	20	7.5	5.5	2.5	2

* not for design Q20
** 4 mm for B_i 38 - 103; 5 mm for B_i 25, 130





Divider system TS3 with height separation consisting of plastic section subdivisions*

Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	η _T min
A	3.5	15	10	2

* not for design Q20

The dividers are fixed with the section subdivision. The entire divider system can be moved in the cross section.



a _x (centre distance of dividers) [mm]									
a _c (usable width of inner chamber) [mm]									
15	20	25	30	35	40	45	55	65	75
10	15	20	25	30	35	40	50	60	70

Order example

TS3

A

2

K1

34

VR1

⋮

⋮

⋮

K4

38

VR3

Divider system

Version

η_T

Chamber

a_x

Height separation

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series





TKP35 series

TKK series

EasyTrax® series

Universal end connectors UMB – plastic (standard)


The universal mounting brackets (UMB) are made from plastic and can be mounted **from above, from below or on the face side**.




Recommended tightening torque:
5 Nm for screws M5 - 8.8

Assembly options

B_i [mm]	n_z
25	2
38	3
58	5
78	7
103	9
130	11



The end connectors are optionally also available **with** strain relief comb (1 on each side). Please state when ordering.



Connection point
F – fixed point
M – driver


Connection type
U – Universal mounting bracket

Order example


	UMB	F	U
	UMB	M	U
	End connector	Connection point	Connection type

Single-part end connectors short – plastic


The plastic end connectors can be connected **from above or below**. The connection type can be changed by altering the position of the end connector.



B_i: 25



B_i: 38-130




Recommended tightening torque:
6 Nm for screws M6 – 8.8

▲ Assembly options

B _i [mm]	n _z
25	2 x 2
38	2 x 3
58	2 x 4
78	2 x 6
103	2 x 8
130	2 x 10

The end connectors are optionally also available **without** strain relief comb (except B_i 25). Please state when ordering.



Connection point
F – fixed point
M – driver

Connection type
A – threaded joint outside (standard)
I – threaded joint inside
H – threaded joint, rotated 90° to the outside
K – threaded joint, rotated 90° to the inside

Order example

End connector	F	A
End connector	M	A
End connector	Connection point	Connection type

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series




TKP35 series

TKK series

EasyTrax® series

Single-part end connectors long – plastic

The plastic end connectors can be connected **from above or below** and allow a **1:1 replacement of the UNIFLEX 0455 in the connection area**. The connection type can be changed by altering the position of the end connector.


B_i: 25B_i: 38-130

▲ Assembly options




Recommended tightening torque:
6 Nm for screws M6 - 8.8 and washers

B _i [mm]	n ₂
25	2 x 2
38	2 x 3
58	2 x 4
78	2 x 6
103	2 x 8
130	2 x 10



The end connectors are optionally also available **without** strain relief comb (except B_i 25). Please state when ordering.



Connection point

F – fixed point
M – driver

Connection type

A – threaded joint outside (standard)
I – threaded joint inside
H – threaded joint, rotated 90° to the outside
K – threaded joint, rotated 90° to the inside

Order example



End connector U0455

F

A


End connector U0455

M

A

End connector

Connection point Connection type



Subject to change without notice.

EasyTrax®
series

TKK
series

TKP35
series

UNIFLEX
Advanced
series

QuickTrax®
series

MONO
series

Materials
information

Configuration
guidelines

Cable carrier
configuration

Cable carrier

UA1555



Pitch
55.5 mm



Inner height
38 mm



Inner widths
50 – 150 mm



Bending radii
63 – 200 mm

Stay variants



Design 020 page 174

Closed frame

- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Design 030 page 175

Frame with outside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Outside:** openable and detachable.



Design 040 page 176

Frame with inside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Inside:** openable and detachable.

Additional product information online




Installation instructions, etc.:
Additional info via your smartphone or
check online at
[tsubaki-kabelschlepp.com/
downloads](http://tsubaki-kabelschlepp.com/downloads)



Configure your cable carrier here:
online-engineer.de

Unsupported arrangement




KR [mm]	H [mm]	H _z [mm]	L _B [mm]	U _B [mm]
63	176	216	309	145
80	210	240	362	165
100	250	280	425	185
125	300	330	504	210
160	370	400	614	245
200	450	480	740	285

Load diagram for unsupported length depending on the additional load.

Sagging of the cable carrier is technically permitted for extended travel lengths, depending on the specific application.

Intrinsic cable carrier weight $q_k = 1.32 \text{ kg/m}$ with $B_i 100 \text{ mm}$. For other inner widths, the maximum additional load changes.



Speed
up to 9 m/s



Acceleration
up to 45 m/s^2




Travel length
up to 6.3 m



Additional load
up to 10 kg/m

Gliding arrangement | GO module with chain links optimized for gliding



KR [mm]	H [mm]	GO module RKR [mm]	L _B [mm]	U _B [mm]
63	150	250	939	458
80	150	250	994	473
100	150	250	1105	510
125	150	250	1272	567
160	150	250	1438	612
200	150	250	1771	730



Speed
up to 3 m/s



Acceleration
up to 20 m/s^2



Travel length
up to 125 m



Additional load
up to 10 kg/m



The gliding cable carrier must be guided in a channel.
See p. 866.

The GO module mounted on the driver is a defined sequence of 5 adapted KR/RKR link plates.

Glide shoes must be used for gliding applications.

Only designs 020 and 030 can be used for a gliding arrangement.

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series

TKK series

EasyTrax® series

Stay variant 020 – closed frame


- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 50 – 150 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_g [mm]	h_g' [mm]	B_i [mm]			B_k [mm]	B_{EF} [mm]	KR [mm]				q_k [kg/m]
38	50	53	50	75	100	$B_i + 18$	$B_i + 22$	63	80	100	125	1.13 – 1.52
			125	150				160	200			




Order example



UA1555 Type	·	020 Stay variant	·	125 B_i [mm]	·	160 KR [mm]	·	1887 L_k [mm]	·	VS Stay arrangement
----------------	---	---------------------	---	-------------------	---	------------------	---	--------------------	---	------------------------

Stay variant 030 – with outside opening and detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » Swivable and detachable left or right in any position.
- » **Outside:** openable and detachable.



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_g [mm]	$h_{g'}$ [mm]	B_i [mm]			B_k [mm]	B_{EF} [mm]	KR [mm]				q_k [kg/m]
38	50	53	50	75	100	$B_i + 18$	$B_i + 22$	63	80	100	125	1.13 – 1.51
			125	150				160	200			

Order example

 UA1555 . 030 . 125 . 160 . 1887 . VS
Type Stay variant B_i [mm] KR [mm] L_k [mm] Stay arrangement

Cable carrier
Cable carrier configuration
Configuration guidelines
Materials information
MONO series
QuickTrax® series
UNIFLEX Advanced series
TKP35 series
TKK series
EasyTrax® series

Stay variant 040 – with inside opening and detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » Swivable and detachable left or right in any position.
- » **Inside:** openable and detachable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 50 – 150 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.



Design 040 is not suitable for gliding arrangements.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h _i [mm]	h _G [mm]	B _i [mm]			B _k [mm]	KR [mm]				q _k [kg/m]
38	50	50	75	100	B _i + 18	63	80	100	125	1.13 – 1.52
		125	150			160	200			

Order example



UA1555

Type

040

Stay variant

125

B_i [mm]

160

KR [mm]

1887

L_k [mm]

VS

Stay arrangement

Divider systems

The divider system is mounted on every 2nd chain link as a standard.


As a standard, dividers or the complete divider system (dividers with height separations) are movable in the cross section (**version A**).

For applications with lateral acceleration and lying on the side, divider with arresting cams are available.
The locking cams click into place in the locking grids in the stays (**version B**).

Divider system TS0 without height separation

Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	a _x grid [mm]	η _T min
A	5	10	7.5	-	-
B*	5	10	7.5	2.5	-


Number of dividers for design 020 depending on B_i
* not for design 020



Divider system TS1 with continuous height separation*

Vers.	a _T min [mm]	a _T max [mm]	a _x min [mm]	a _c min [mm]	a _x grid [mm]	η _T min
A	5	20	10	7.5	-	2
B	5	20.5	10	7.5	2.5	2

* not for design 020





Divider system TS3 with height separation consisting of plastic section subdivisions*

Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	η _T min
A	5	15	10	2

* not for design 020

The dividers are fixed with the partitions. The entire divider system can be moved in the cross section.



a _x (centre distance of dividers) [mm]									
a _c (usable width of inner chamber) [mm]									
15	20	25	30	35	40	45	55	65	75
10	15	20	25	30	35	40	50	60	70

Order example



TS3	A	2	K1	34	VR1
			⋮	⋮	⋮
			K4	38	VR3
Divider system	Version	η _T	Chamber	a _x	Height separation

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series



TKP35 series

TKK series

EasyTrax® series

Universal end connectors UMB – plastic (standard)


The universal mounting brackets (UMB) are made from plastic and can be mounted **from above, from below or on the face side**.



▲ Assembly options

 Recommended tightening torque:
5 Nm for screws M5 – 8.8

B_1 [mm]	n_2
50	2 x 3
75	2 x 5
90	2 x 6
100	2 x 7
125	2 x 9
150	2 x 11




The end connectors are optionally also available **with** strain relief comb or **with** C-rail Art. no. 3931 (1 on each side) for clamps. Please state when ordering.

UNIFLEX
Advanced
series

TKP35
series

TKK
series

EasyTrax®
series



Connection point
F – fixed point
M – driver

Connection type
U – Universal mounting bracket



Order example

	UMB	•	F	U
	UMB	•	M	U
	End connector		Connection point	Connection type

 We recommend the use of strain reliefs at the driver and fixed point. See from p. 924.

Single-part end connectors short – plastic


The plastic end connectors can be **connected from above or below**. The connection type can be changed by altering the position of the end connector.




▲ Assembly options

 Recommended tightening torque:
6 Nm for screws M6 - 8.8

B_i [mm]	n_z
50	2 x 4
75	2 x 6
100	2 x 8
125	2 x 10
150	2 x 12



The end connectors are optionally also available **without** strain relief comb.
Please state when ordering.



Connection point

- F – fixed point
- M – driver

Connection type

- A – threaded joint outside (standard)
- I – threaded joint inside
- H – threaded joint, rotated 90° to the outside
- K – threaded joint, rotated 90° to the inside

Order example





End connector	F	A
End connector	M	A
End connector	Connection point	Connection type

Cable carrier	Cable carrier configuration	Configuration guidelines	Materials information	MONO series	QuickTrax® series	UNIFLEX Advanced series	TKP35 series	TKK series	EasyTrax® series
---------------	-----------------------------	--------------------------	-----------------------	-------------	-------------------	-------------------------	--------------	------------	------------------

Single-part end connectors long – plastic


The plastic end connectors can be connected **from above or below** and allow a **1:1 replacement of the UNIFLEX 0555 in the connection area**. The connection type can be changed by altering the position of the end connector.




▲ Assembly options

Recommended tightening torque:
6 Nm for screws M6 – 8.8 and washers

B_1 [mm]	n_z
50	2 x 4
75	2 x 6
100	2 x 8
125	2 x 10
150	2 x 12



The end connectors are optionally also available **without** strain relief comb. Please state when ordering.



Connection point

F – fixed point
M – driver

Connection type

A – threaded joint outside (standard)
I – threaded joint inside
H – threaded joint, rotated 90° to the outside
K – threaded joint, rotated 90° to the inside

Order example

	End connector U0555	F	A
	End connector U0555	M	A
	End connector	Connection point	Connection type



Subject to change without notice.

EasyTrax®
series

TKK
series

TKP35
series

UNIFLEX
Advanced
series

QuickTrax®
series

MONO
series

Materials
information

Configuration
guidelines

Cable carrier
configuration

Cable carrier

UA1665



Pitch
66.5 mm



Inner height
44 mm



Inner widths
50 – 250 mm



Bending radii
75 – 300 mm

Stay variants



Design 020 page 184

Closed frame

- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Design 030 page 185

Frame with outside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Outside:** openable and detachable.



Design 040 page 186

Frame with inside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Inside:** openable and detachable.



Design RMAI page 188

Mounting frame stay

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Inside:** threaded joint easy to release.




Design RMAO page 190

Mounting frame stay

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Outside:** threaded joint easy to release.

Unsupported arrangement



KR [mm]	H [mm]	H _z [mm]	L _B [mm]	U _B [mm]
75	210	245	369	172
100	260	295	448	197
120	300	335	511	217
140	340	375	574	237
200	460	495	762	297
250	560	595	919	347
300	660	695	1076	397

Load diagram for unsupported length depending on the additional load.

Sagging of the cable carrier is technically permitted for extended travel lengths, depending on the specific application.

Intrinsic cable carrier weight $q_k = 2.43 \text{ kg/m}$ with $B_3 200 \text{ mm}$. For other inner widths, the maximum additional load changes.



Speed
up to 8 m/s




Acceleration
up to 40 m/s^2




Travel length
up to 7 m



Additional load
up to 15 kg/m



Gliding arrangement | GO module with chain links optimized for gliding



KR [mm]	H [mm]	GO module RKR [mm]	L _B [mm]	U _B [mm]
75	180	300	1118	546
100	180	300	1251	593
120	180	300	1318	609
140	180	300	1450	654
200	180	300	1783	753
250	180	300	2182	864
300	180	300	2581	1035



Speed
up to 3 m/s



Acceleration
up to 15 m/s^2



Travel length
up to 150 m



Additional load
up to 15 kg/m



The gliding cable carrier must be guided in a channel.
See p. 866.

The GO module mounted on the driver is a defined sequence of 5 adapted KR/RKR link plates.

Glide shoes must be used for gliding applications.

Only designs 020 and 030 can be used for a gliding arrangement.

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series

TKK series

EasyTrax® series

Stay variant 020 – closed frame


- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 50 – 250 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_g [mm]	h_g' [mm]	B_i [mm]					B_k [mm]	B_{EF} [mm]	KR [mm]				q_k [kg/m]
44	60	63	50	75	100	125	150	$B_i + 22$	$B_i + 27$	75	100	120	140	1.67 – 2.76
			175	200	225	250				200	250	300		

Order example



UA1665
Type

020
Stay variant

125
 B_i [mm]

140
 KR [mm]

2660
 L_k [mm]

VS
Stay arrangement

Stay variant 030 – with outside opening and detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » Swivable and detachable left or right in any position.
- » **Outside:** openable and detachable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 50 – 250 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_g [mm]	h_g' [mm]	B_i [mm]					B_k [mm]	B_{EF} [mm]	KR [mm]				q_k [kg/m]
44	60	63	50	75	100	125	150	$B_i + 22$	$B_i + 27$	75	100	120	140	1.67 – 2.70
			175	200	225	250				200	250	300		

Order example



UA1665	030	125	140	2660	VS
Type	Stay variant	B_i [mm]	KR [mm]	L_k [mm]	Stay arrangement

Stay variant 040 – with inside opening and detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » Swivable and detachable left or right in any position.
- » **Inside:** openable and detachable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 50 – 250 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.



Design 040 is not suitable for gliding arrangements.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_g [mm]	B_i [mm]					B_k [mm]	KR [mm]				q_k [kg/m]
44	60	50	75	100	125	150	$B_i + 22$	75	100	120	140	1.67 – 2.70
		175	200	225	250			200	250	300		

Order example



UA1665
Type

040
Stay variant

125
 B_i [mm]

140
 KR [mm]

2660
 L_k [mm]

VS
Stay arrangement



Subject to change without notice.

EasyTrax®
series

TKK
series

TKP35
series

UNIFLEX
Advanced
series

QuickTrax®
series

MONO
series

Materials
information

Configuration
guidelines

Cable carrier
configuration

Cable carrier


- » Weight-optimized plastic frame with particularly high torsional rigidity.
- » Plastic stays and aluminum profile bars with plastic mounting frame stays for guiding very large cable diameters.
- » **Inside:** threaded joint easy to release.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_j 125 – 200 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k
rounded to pitch t

h_i [mm]	h_G [mm]	H_i [mm]		B_i [mm]		B_k [mm]	B_{EF} [mm]	KR [mm]				q_k^* [kg/m]
44	60	114	139	125	150	$B_i + 22$	$B_i + 27$	75	100	120	140	3.10 – 3.95
		164	189	175	200			200	250	300		

* indicated according to standard pitch

Order example



UA1665
Type

RMAI
Stay variant

150
Bi [mm]140
KR [mm]2660
L_k [mm]

VS
Stay arrangement

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO
series

series
QuickTrax®UNIFLEX
Advanced
seriesTKP35
series

TKK series

series
EasyTrax®

RMAI – assembly to the inside:

standard pitch, mounting frame stay on every 4th stay,
no screw fixing.

Gliding application is not possible when using assembly
version RMAI.


Observe minimum KR:

H_i = 114 mm: KR_{min} = 200 mm

H_i = 139 mm: KR_{min} = 250 mm

H_i = 164 mm: KR_{min} = 300 mm

H_i = 189 mm: KR_{min} = 300 mm



Cross section mounting frame stay

To achieve a nearly square cross section in the mounting
frame stay, we recommend the following combination of B_i
and H_i:

B _i [mm]	H _i [mm]	KR _{min} [mm]	Stays [mm]
125	114	200	100
150	139	250	125
175	164	300	150
200	189	300	175

Cable carrier

Cable carrier
configuration

Configuration
guidelines

Materials
information

MONO
series

QuickTrax®
series

UNIFLEX
Advanced
series

TKP35
series

TKK
series

EasyTrax®
series



TOTALTRAX® complete systems

Benefit from the advantages of the TOTALTRAX® complete system.
A complete delivery from one source – with a warranty certificate
on request! Learn more at tsubaki-kabelschlepp.com/totaltrax



TRAXLINE® cables for cable carriers

Hi-flex electric cables which were specially developed, optimised and
tested for use in cable carriers can be found at
tsubaki-kabelschlepp.com/traxline.

Stay variant RMAO – mounting frame stay


- » Weight-optimized plastic frame with particularly high torsional rigidity.
- » Plastic stays and aluminum profile bars with plastic mounting frame stays for guiding very large cable diameters.
- » **Outside:** threaded joint easy to release.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 125 – 200 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k
rounded to pitch t

h_i [mm]	h_g [mm]	H_i [mm]	B_i [mm]	B_k [mm]	B_{EF} [mm]	KR [mm]	q_k^* [kg/m]
44	60	114 139 164 189	125 150 175 200	$B_i + 22$	$B_i + 27$	75 100 120 140 200 250 300	3.58 – 4.66

* indicated according to standard pitch

Order example



UA1665
Type

RMAO
Stay variant

150
 B_i [mm]

140
 KR [mm]

2660
 L_k [mm]

VS
Stay arrangement


RMAO – assembly to the outside:

standard pitch, mounting frame stay on every 2nd stay, screw fixing.

The cable carrier rests on the bars. A bracket must be provided for the fixed point.

Guiding in a **channel is required** for support. Please contact our technical support at technik@kabelschlepp.de to find the corresponding guide channel.

Please note the operating and installation height.



Cross section mounting frame stay

To achieve a nearly square cross section in the mounting frame stay, we recommend the following combination of B_i and H_i:

B _i [mm]	H _i [mm]	KR _{min} [mm]	Stays [mm]
125	114	200	100
150	139	250	125
175	164	300	150
200	189	300	175

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series

TKK series

EasyTrax® series



TOTALTRAX® complete systems

Benefit from the advantages of the TOTALTRAX® complete system. A complete delivery from one source – with a warranty certificate on request! Learn more at tsubaki-kabelschlepp.com/totaltrax



TRAXLINE® cables for cable carriers

Hi-flex electric cables which were specially developed, optimised and tested for use in cable carriers can be found at tsubaki-kabelschlepp.com/traxline.



EasyTrax®
series

TKK
series

TKP35
series

UNIFLEX
Advanced
series

QuickTrax®
series

MONO
series

Materials
information

Configuration
guidelines

Cable carrier
configuration

Cable carrier

Divider systems

The divider system is mounted on every 2nd chain link as a standard.

As a standard, dividers or the complete divider system (dividers with height separations) are movable in the cross section (**version A**).


For applications with lateral acceleration and lying on the side, divider with arresting cams are available.

The locking cams click into place in the locking grids in the stays (**version B**).

Divider system TS0 without height separation

Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	a _x grid [mm]	η _T min
A	5	10	7	-	-
B*	5	10	7	2.5	-


Number of dividers for design 020 depending on B_i
* not for design 020



Divider system TS1 with continuous height separation*

Vers.	a _T min [mm]	a _T max [mm]	a _x min [mm]	a _c min [mm]	a _x grid [mm]	η _T min
A	5	20	10	7	-	2
B	5	20	10	7	2.5	2

* not for design 020





Divider system TS3 with height separation consisting of plastic section subdivisions*

Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	η _T min
A	4	16/40**	8	2

* not for design 020

** for aluminium partitions

The dividers are fixed with the partitions. The entire divider system can be moved in the cross section.



Aluminium partitions in 1 mm increments with a_x > 42 mm are also available.

a _x (centre distance of dividers) [mm]											
a _c (usable width of inner chamber) [mm]											
16	18	23	28	32	33	38	43	48	58	64	68
8	10	15	20	24	25	30	35	40	50	56	60
78	80	88	96	112	128	144	160	176	192	208	
70	72	80	88	104	120	136	152	168	184	200	

When using partitions with a_x > 112 mm, we recommend an additional central support with a **twin divider**. The height separations VD4 and VD5 are not possible when using twin dividers.

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series



TKP35 series

TKK series

EasyTrax® series

Universal end connectors UMB – plastic (standard)


The universal mounting brackets (UMB) are made from plastic and can be mounted **from above, from below or on the face side**.




▲ Assembly options

Recommended tightening torque:
5 Nm for screws M5 – 8.8

B ₁ [mm]	n ₂
50	2 x 3
75	2 x 5
100	2 x 7
125	2 x 9
150	2 x 11
175	2 x 13



The end connectors are also available as an option **with** strain relief comb or **with** C-rail Art. no 3931 (1 on each side) for clamps. Please state when ordering.



Connection point

F – fixed point
M – driver

Connection type

U – Universal mounting bracket

Order example





UMB	F	U
UMB	M	U
End connector	Connection point	Connection type

We recommend the use of strain reliefs at the driver and fixed point. See from p. 924.

Single-part end connectors – plastic


The plastic end connectors can be connected **from above or below**. The connection type can be changed by altering the position of the end connector.




▲ Assembly options

 Recommended tightening torque:
15 Nm for screws M8 – 8.8

B_i [mm]	n_z
50	2 x 4
75	2 x 6
100	2 x 8
125	2 x 10
150	2 x 12
175	2 x 14
200	2 x 16
225	2 x 18
250	2 x 20



The end connectors are optionally also available **without** strain relief comb.
Please state when ordering.



Connection point

- F – fixed point
- M – driver

Connection type

- A – threaded joint outside (standard)
- I – threaded joint inside
- H – threaded joint, rotated 90° to the outside
- K – threaded joint, rotated 90° to the inside

Order example



End connector	F	A
End connector	M	A
End connector	Connection point	Connection type

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series

TKK series

EasyTrax® series

UA1775



Pitch
77.5 mm



Inner height
56 mm



Inner widths
100 – 400 mm



Bending radii
90 – 340 mm

Stay variants



Design 020 page **198**

Closed frame

- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Design 030 page **199**

Frame with outside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Outside:** openable and detachable.




Design 040 page **200**

Frame with inside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Inside:** openable and detachable.

Unsupported arrangement




KR [mm]	H [mm]	H _z [mm]	L _B [mm]	U _B [mm]
90	257	297	438	206
115	307	347	516	231
140	357	397	595	256
165	407	447	673	281
190	457	497	752	306
240	557	597	909	356
285	647	687	1050	401
340	757	797	1223	456

Load diagram for unsupported length depending on the additional load.

Sagging of the cable carrier is technically permitted for extended travel lengths, depending on the specific application.

Intrinsic cable carrier weight $q_k = 3.03 \text{ kg/m}$ with $B_f 150 \text{ mm}$. For other inner widths, the maximum additional load changes.



Speed
up to 10 m/s



Acceleration
up to 35 m/s²




Travel length
up to 6.8 m



Additional load
up to 25 kg/m

Gliding arrangement | GO module with chain links optimized for gliding



KR [mm]	H [mm]	GO module RKR [mm]	L _B [mm]	U _B [mm]
90	231	400	1313	643
115	231	400	1440	688
140	231	400	1575	733
165	231	400	1715	779
190	231	400	1868	828
240	231	400	2225	951
285	231	400	2580	1081
340	231	400	3015	1240



Speed
up to 3 m/s



Acceleration
up to 8 m/s²



Travel length
up to 200 m



Additional load
up to 25 kg/m



The gliding cable carrier must be guided in a channel.
See p. 866.

The GO module mounted on the driver is a defined sequence of 5 adapted KR/RKR link plates.

Glide shoes must be used for gliding applications.

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series

TKK series

EasyTrax® series

Stay variant 020 – closed frame


- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 100 – 400 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_G [mm]	h_G' [mm]	B_i [mm]					B_k [mm]	B_{EF} [mm]	KR [mm]			q_k [kg/m]
			100	125	150	175	200			90	115	140	
56	77	81.6	225	250	275	300	325	$B_i + 26$	$B_i + 30$	165	190	240	2.844 – 4.239
			350	375	400					285	340		

Order example



UA1775
Type

020
Stay variant

150
 B_i [mm]

140
 KR [mm]

3100
 L_k [mm]

VS
Stay arrangement

Stay variant 030 – with outside opening and detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » Swivable and detachable left or right in any position.
- » **Outside:** openable and detachable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 100 – 400 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h _i [mm]	h _G [mm]	h _{G'} [mm]	B _i [mm]					B _k [mm]	B _{EF} [mm]	KR [mm]			q _k [kg/m]
56	77	81.6	100	125	150	175	200	B _i + 26	B _i + 30	90	115	140	2.831 – 4.224
			225	250	275	300	325			165	190	240	
			350	375	400					285	340		

Order example



UA1775 Type · 030 Stay variant · 150 B_i [mm] · 140 KR [mm] · 3100 L_k [mm] · VS Stay arrangement

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series

TKK series

EasyTrax® series

Stay variant 040 – with inside opening and detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » Swivable and detachable left or right in any position.
- » **Inside:** openable and detachable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 100 – 400 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.



Design 040 is not suitable for a gliding arrangements without the use of gliding shoes.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_G [mm]	h_G' [mm]	B_i [mm]					B_k [mm]	B_{EF} [mm]	KR [mm]			q_k [kg/m]
56	77	81.6	100	125	150	175	200	$B_i + 26$	$B_i + 30$	90	115	140	2.831 – 4.224
			225	250	275	300	325			165	190	240	
			350	375	400					285	340		

Order example



UA1775
Type

040
Stay variant

150
 B_i [mm]

140
 KR [mm]

3100
 L_k [mm]

VS
Stay arrangement

Divider systems

The divider system is mounted on every 2nd chain link as a standard.

As a standard, dividers or the complete divider system (dividers with height separations) are movable in the cross section (**version A**).


For applications with lateral acceleration and lying on the side, divider with arresting cams are available.

The locking cams click into place in the locking grids in the stays (**version B**).

Divider system TS0 without height separation

Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	a _x grid [mm]	n _T min
A	5	10	7	-	-
B	5	10	7	2.5	-


Number of dividers for design Q20 depending on B_i



Divider system TS1 with continuous height separation*

Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	a _x grid [mm]	n _T min
A	5	10	7	-	2
B	5	10	7	2.5	2

* not for design Q20



Order example



TS1

A

3

VD0

⋮

VD1

Divider system

Version

n_T

Height separation

Please state the designation of the divider system (**TS0, TS1,...**), the version, and the number of dividers per cross section [n_T].

When using divider systems with height separation (**TS1**), please additionally state the position (e.g. VD1) viewed from the left driver belt. You are welcome to add a sketch to your order.

Cable carrier

Cable carrier configuration

Configuration guidelines

Materials information

MONO series

QuickTrax® series

UNIFLEX Advanced series

TKP35 series


TKK series

EasyTrax® series


Divider system TS3 with height separation consisting of plastic partitions

As a standard, the divider **version A** is used for vertical partitioning within the cable carrier. The complete divider system can be moved within the cross section.

Divider version A





End divider



Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	η _T min
A	5/2*	14	10	2

* For End divider

The dividers are fixed by the partitions, the complete divider system is movable in the cross section.



a _x (center distance of dividers) [mm]																			
a _c (nominal width of inner chamber) [mm]																			
14	16	19	23	24	28	29	32	33	34	38	39	43	44	48	49	54	58	59	64
10	12	15	19	20	24	25	28	29	30	34	35	39	40	44	45	50	64	68	69
58	59	64	68	69	74	78	79	80	84	88	89	94	96	99	112	54	55	60	64
54	55	60	64	65	70	74	75	76	80	84	85	90	92	95	108	65	70	74	75

When using **partitions with a_x > 49 mm** we recommended an additional preferential central support.

Order example



TS3

A

3

K1

34

VR1

⋮

K4

38

VR3

Divider system

Version

η_T

Chamber

a_x



Height separation

Please state the designation of the divider system (**TS0, TS1,...**), version and number of dividers per cross section [η_T]. In addition, please also enter the chambers [K] from left to right, as well as the assembly distances [a_T/a_x] (as seen from the driver).

If using divider systems with height separation (**TS1, TS3**) please also state the positions [e.g. VD23] viewed from the left driver belt. You are welcome to add a sketch to your order.

Universal end connectors UMB – plastic (standard)


The universal mounting brackets (UMB) are made from plastic and can be mounted **from above, from below or on the face side**.




▲ Assembly options

Recommended tightening torque:
27 Nm for screws M8

B_i [mm]	n_z
100	2 x 7
125	2 x 9
150	2 x 11
175	2 x 13



The end connectors are also available as an option **with** strain relief comb or **with** C-rail Art. no 3931 (1 on each side) for clamps. Please state when ordering.



Connection point
F – fixed point
M – driver

Connection type
U – Universal mounting bracket

Order example



UMB	.	F	U
UMB	.	M	U
End connector		Connection point	Connection type

We recommend the use of strain reliefs at the driver and fixed point. See from p. 924.

Cable carrier
Cable carrier configuration
Configuration guidelines
Materials information
MONO series
QuickTrax® series
UNIFLEX Advanced series
TKP35 series
TKK series
EasyTrax® series

UA1995



Pitch
99.5 mm



Inner height
80 mm



Inner widths
85 – 250 mm



Bending radii
150 – 500 mm

Stay variants



Design 020 page **206**

Closed frame

- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Design 030 page **207**

Frame with outside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Outside:** release by rotating 90°.



Design 040 page **208**

Frame with inside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Inside:** release by rotating 90°.




Design 070 page **209**

Frame with outside and inside detachable stays

- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** release by rotating 90°.

Unsupported arrangement



KR [mm]	H [mm]	H _z [mm]	L _B [mm]	U _B [mm]
150	410	440	680	250
210	530	560	860	310
250	610	640	990	350
300	710	740	1150	400
350	810	840	1300	450
400	910	940	1460	500
500	1110	1140	1770	600

Load diagram for unsupported length depending on the additional load.

Sagging of the cable carrier is technically permitted for extended travel lengths, depending on the specific application.

Intrinsic cable carrier weight $q_k = 3.85 \text{ kg/m}$ with $B_i 196 \text{ mm}$. For other inner widths, the maximum additional load changes.



Speed
up to 10 m/s




Acceleration
up to 25 m/s^2




Travel length
up to 9 m



Additional load
up to 50 kg/m



Gliding arrangement | GO module with chain links optimized for gliding*



KR [mm]	H [mm]	GO module RKR [mm]	L _B [mm]	U _B [mm]
150	330	400	1805	890
210	330	400	2180	1010
250	330	400	2390	1070
300	330	400	2690	1160
350	330	400	3090	1310
400	330	400	3490	1450
500	330	400	4280	1740



Speed
up to 8 m/s



Acceleration
up to 20 m/s^2



Travel length
up to 200 m



Additional load
up to 50 kg/m



The gliding cable carrier must be guided in a channel.
See p. 866.

The GO module mounted on the driver is a defined sequence of 5 adapted KR/RKR link plates.

Glide shoes must be used for gliding applications.

Stay variant 020 – closed frame


- » Weight-optimised, closed plastic frame with particularly high torsional rigidity.
- » **Outside/inside:** not openable.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 85 – 250 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_g [mm]	h_g' [mm]	B_i [mm]				B_k [mm]	B_{EF} [mm]	KR [mm]				q_k [kg/m]
80	110	116.5	85	125	138	150	$B_i + 30$	$B_i + 36$	150	210	250	300	3.860 – 3.861
			180	196	225	250			350	400	500		

Order example



UA1995
Type

020
Stay variant

150
 B_i [mm]

210
 KR [mm]

3582
 L_k [mm]

VS
Stay arrangement

Stay variant 030 –
with outside detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Outside:** release by rotating 90°.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 85 – 250 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h_i [mm]	h_g [mm]	$h_{g'}$ [mm]	B_i [mm]				B_k [mm]	B_{EF} [mm]	KR [mm]				q_k [kg/m]
80	110	116.5	85	125	138	150	$B_i + 30$	$B_i + 36$	150	210	250	300	3.833 – 3.834
			180	196	225	250			350	400	500		

Order example



UA1995 . 030 . 150 . 210 . 3582 . VS
Type Stay variant B_i [mm] KR [mm] L_k [mm] Stay arrangement

Cable carrier
Cable carrier configuration
Configuration guidelines
Materials information
MONO series
QuickTrax® series
UNIFLEX Advanced series
TKP35 series
TKK series
EasyTrax® series

Stay variant 040 –
with inside detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Inside:** release by rotating 90°.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 85 – 250 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.



Design 040 is not suitable for a gliding arrangements without the use of gliding shoes.

Calculating the
cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k
rounded to pitch t

h_i [mm]	h_g [mm]	h_g' [mm]	B_i [mm]	B_k [mm]	B_{EF} [mm]	KR [mm]	q_k [kg/m]
80	110	116.5	85 125 138 150 180 196 225 250	$B_i + 30$	$B_i + 36$	150 210 250 300 350 400 500	3.833 – 3.834

Order example



UA1995 Type	040 Stay variant	150 B_i [mm]	210 KR [mm]	3582 L_k [mm]	VS Stay arrangement
----------------	---------------------	-------------------	------------------	--------------------	------------------------

Stay variant 070 – with outside and inside detachable stays


- » Weight-optimised plastic frame with particularly high torsional rigidity.
- » **Outside/Inside:** release by rotating 90°.



Stay arrangement on each chain link (**VS: fully-stayed**)



B_i 85 – 250 mm



The maximum cable diameter strongly depends on the bending radius and the desired cable type. Please contact us.

Design 070 is not suitable for a gliding arrangements without the use of gliding shoes.

Calculating the cable carrier length

Cable carrier length L_k

$$L_k \approx \frac{L_S}{2} + L_B$$

Cable carrier length L_k rounded to pitch t

h _i [mm]	h _g [mm]	h _{g'} [mm]	B _i [mm]				B _k [mm]	B _{EF} [mm]	KR [mm]				q _k [kg/m]
80	110	116.5	85	125	138	150	B _i + 30	B _i + 36	150	210	250	300	3.852 – 3.853
			180	196	225	250			350	400	500		

Order example



UA1995 . 070 . 150 . 210 . 3582 . VS
Type Stay variant B_i [mm] KR [mm] L_k [mm] Stay arrangement

Cable carrier
Cable carrier configuration
Configuration guidelines
Materials information
MONO series
QuickTrax® series
UNIFLEX Advanced series
TKP35 series
TKK series
EasyTrax® series

Divider systems

The divider system is mounted on every 2nd chain link as a standard.

As a standard, dividers or the complete divider system (dividers with height separations) are movable in the cross section (**version A**).


For applications with lateral acceleration and lying on the side, divider with arresting cams are available.

The locking cams click into place in the locking grids in the stays (**version B**).

Divider system TS0 without height separation

Vers.	a _T min [mm]	a _X min [mm]	a _C min [mm]	a _X grid [mm]	η _T min
A	10	16	12	-	-
B	10	17.5	13.5	2.5	-


Number of dividers for design 020 depending on B₁



Divider system TS1 with continuous height separation*

Vers.	a _T min [mm]	a _X min [mm]	a _C min [mm]	a _X grid [mm]	η _T min
A	10	16	12	-	2
B	10	17.5	13.5	2.5	2

* not for design 020



Order example



TS1

A

3

VD0

⋮

VD1

Divider systemVersionη_THeight separation


Please state the designation of the divider system (**TS0, TS1,...**), the version, and the number of dividers per cross section [η_T].

When using divider systems with height separation (**TS1**), please additionally state the position (e.g. VD1) viewed from the left driver belt. You are welcome to add a sketch to your order.


Divider system TS3 with height separation consisting of plastic partitions

As a standard, the divider **version A** is used for vertical partitioning within the cable carrier. The complete divider system can be moved within the cross section.

Divider version A





End divider



Vers.	a _T min [mm]	a _x min [mm]	a _c min [mm]	n _T min
A	8 / 4*	14	10	2

Number of dividers for design 020 depending on B_i
* For End divider

The dividers are fixed by the partitions, the complete divider system is movable in the cross section.



a _x (center distance of dividers) [mm]															
a _c (nominal width of inner chamber) [mm]															
14	16	19	23	24	28	29	32	33	34	38	39	43	44	48	54
10	12	15	19	20	24	25	28	29	30	34	35	39	40	44	50
58	59	64	68	69	74	78	79	80	84	88	89	94	96	99	112
54	55	60	64	65	70	74	75	76	80	84	85	90	92	95	108

An additional central support is required when using plastic partitions with a_x > 49 mm.

Order example

TS3

A

3

K1

34

VR1

⋮

⋮

⋮

K4

38

VR3

Divider system

Version

n_T

Chamber

a_x


Height separation

Please state the designation of the divider system (**TS0, TS1,...**), version and number of dividers per cross section [n_T]. In addition, please also enter the chambers [K] from left to right, as well as the assembly distances [a_T/a_x] (as seen from the driver).

If using divider systems with height separation (**TS1, TS3**) please also state the positions [e.g. VD23] viewed from the left driver belt. You are welcome to add a sketch to your order.



Cable carrier
Cable carrier configuration
Configuration guidelines
Materials information
MONO series
QuickTrax® series
UNIFLEX Advanced series
TKP35 series
TKK series
EasyTrax® series

EasyTrax® series	TKK series	TKP35 series	UNIFLEX Advanced series		QuickTrax® series	MONO series	Materials information	Configuration guidelines	Cable carrier configuration	Cable carrier
---------------------	---------------	-----------------	-------------------------------	--	----------------------	----------------	--------------------------	-----------------------------	--------------------------------	---------------




Universal end connectors UMB – plastic (standard)

The universal mounting brackets (UMB) are made from plastic and can be mounted **from above, from below or on the face side**.



▲ Assembly options


 Recommended tightening torque:
27 Nm for screws M8



Connection point
F – fixed point
M – driver

Connection type
U – Universal mounting bracket

Order example



 We recommend the use of strain reliefs at the driver and fixed point. See from p. 924.

Cable carrier
Cable carrier configuration
Configuration guidelines
Materials information
MONO series
QuickTrax® series
UNIFLEX Advanced series
TKP35 series
TKK series
EasyTrax® series

Additional product information online



Installation instructions, etc.:
Additional info via your smartphone or check online at
tsubaki-kabelschlepp.com/downloads



Configure your cable carrier here:
online-engineer.de